

**Product** 16135**Number:****Order** 39PAR30/HAL/WFL50/DL 120V**Abbreviation:****General** Tungsten Halogen PAR30 Reflector Lamp 39Watt 120Volt Medium**Description:** Base WideFlood50 Beam Double Life**\* Full Case Required****Product Information**

|                                   |                                    |
|-----------------------------------|------------------------------------|
| Abbrev. With Packaging Info.      | 39PAR30HALWFL50DL 120V 10/CS I/SKU |
| Approx. Lumens                    | 520                                |
| Average Rated Life (hr)           | 3000                               |
| Base                              | E26 Medium                         |
| Beam Angle (deg)                  | 50                                 |
| Beam Type                         | WFL                                |
| Bulb                              | PAR30                              |
| Centerbeam Candlepower (cp)       | 600                                |
| Class                             | C (gas)                            |
| Color Rendering Index (CRI)       | 100                                |
| Color Temperature/CCT (K)         | 2800                               |
| Diameter (in)                     | 3.752                              |
| Diameter (mm)                     | 95.30                              |
| Ecologic                          | YES                                |
| Family Brand Name                 | Halogen Par30                      |
| Filament                          | CC-8                               |
| Horizontal Beam Angle (deg)       | 50                                 |
| Lamp Finish                       | Reflector                          |
| Maximum Overall Length - MOL (in) | 3.625                              |
| Maximum Overall Length - MOL (mm) | 92.075                             |
| Nominal Voltage (V)               | 120.00                             |
| Nominal Wattage (W)               | 39.00                              |
| Vertical Beam Angle (deg)         | 50                                 |

**Footnotes**

- State of the Art SPL Optics

- In base up operation, heat may eventually deteriorate paper-lined or plastic sockets.