



GE
Lighting

20117 - 200PAR46/3NSP

GE PAR46 - Narrow Spot; Street Lighting

Photo
Not Available

Photo
Not Available



CAUTIONS & WARNINGS

Warning

- Risk of Fire
 - Keep combustible materials away from lamp.
- Risk of Electric Shock
 - Turn power off before inspection, installation or removal.
- Unexpected lamp rupture may cause injury, fire, or property damage
 - Use in enclosed fixture rated for this product.
 - Avoid direct water/liquid contact.

NOTES

- For use with heat-resistant connector supported by bulb rim or metal shell of base.
- Lamp is made of heat resistant glass (HRG).

GENERAL CHARACTERISTICS

Lamp Type	Sealed Beam - PAR
Bulb	PAR46
Base	Medium Side Prong
Filament	CC-13
Rated Life (NOM)	2000.0 h
Primary Application	Narrow Spot; Street Lighting

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	2270.0
Beam Spread - Horizontal	23.0 - 10.0 °/12.0 - 50.0 °
Beam Spread - Vertical	19.0 - 10.0 °/8.0 - 50.0 °
Center Beam Candlepower (CBCP) (NOM)	31000.0
Color Temperature (NOM)	2750.0 K
Nominal Initial Lumens per Watt (NOM)	11.35

ELECTRICAL CHARACTERISTICS

Wattage (NOM)	200.0
Voltage (NOM)	130.0

DIMENSIONS

Maximum Overall Length (MOL) (NOM)	4.000 in(101.6 mm)
Bulb Diameter (DIA) (NOM)	5.750 in(146.0 mm)

PRODUCT INFORMATION

Product Code	20117
Description	200PAR46/3NSP
Standard Package	Case
Standard Package GTIN	00043168201179
Standard Package Quantity	12
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	12
UPC	043168201162