



GE  
Lighting

## 20849 - 300PAR56/WFL

GE PAR56 - Wide Flood





Photo  
Not Available



### CAUTIONS & WARNINGS

#### Warning

- Risk of Fire
  - Keep combustible materials away from lamp.
- Risk of Electric Shock
  - Turn power off before inspection, installation or removal.
- Unexpected lamp rupture may cause injury, fire, or property damage
  - Use in enclosed fixture rated for this product.
  - Avoid direct water/liquid contact.

### NOTES

- For use with heat-resistant connector supported by bulb rim or metal shell of base.
- Lamp is made of heat resistant glass (HRG).

### GENERAL CHARACTERISTICS

Lamp Type	Sealed Beam - PAR
Bulb	PAR56
Base	Mogul End Prong (GX16d)
Filament	CC-13
Rated Life (NOM)	2000.0 h
Primary Application	Wide Flood

### PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	3840.0
Beam Spread - Horizontal	57.0 - 10.0 °/37.0 - 50.0 °
Beam Spread - Vertical	27.0 - 10.0 °/18.0 - 50.0 °
Center Beam Candlepower (CBCP) (NOM)	11000.0
Color Temperature (NOM)	2750.0 K
Nominal Initial Lumens per Watt (NOM)	12.8

### ELECTRICAL CHARACTERISTICS

Wattage (NOM)	300.0
Voltage (NOM)	120.0

### DIMENSIONS

Maximum Overall Length (MOL) (NOM)	5.000 in(127.0 mm)
Bulb Diameter (DIA) (NOM)	7.000 in(177.8 mm)

### PRODUCT INFORMATION

Product Code	20849
Description	300PAR56/WFL
Standard Package	Case
Standard Package GTIN	10043168208496
Standard Package Quantity	12
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	12
UPC	043168208499