

# 43705 - Q300T4/CL

GE Quartzline® T4 - Stage & Studio This product is no longer manufactured.

## **GENERAL CHARACTERISTICS**

Lamp Type Bulb Base

Filament Rated Life (NOM) **Primary Application**  Halogen - Double-Ended Τ4 **Recessed Single Contact** (R7s) CC-8 2000.0 h Stage & Studio

## **PHOTOMETRIC CHARACTERISTICS**

Initial Lumens (NOM) 5650.0 Color Temperature (NOM) 2900.0 K Nominal Initial Lumens per Watt (NOM)

18.83333

## **ELECTRICAL CHARACTERISTICS**

Wattage (NOM)	300.0
Voltage (NOM)	120.0

## DIMENSIONS

Maximum Overall Length 3.125 in(79.4 mm) (MOL) (NOM) Bulb Diameter (DIA) (NOM) Light Center Length (LCL) (NOM)

0.500 in(12.7 mm) 2.250 in(57.2 mm)

#### **PRODUCT INFORMATION**

Product Code Description ANSI Code Standard Package Standard Package GTIN Standard Package Quantity Sales Unit No Of Items Per Sales Unit No Of Items Per Standard Package UPC

43705 Q300T4/CL EHP Case 10043168437056 24 Unit 1 24

043168437059



#### **CAUTIONS & WARNINGS**

#### Caution

- Lamp emits UV radiation which may cause eye/skin irritation. RG-1
- Minimize exposure.
- Lamp may shatter and cause injury if broken
- Dispose of lamp in a closed container.
- Do not use lamp if outer glass is scratched or broken.

#### Warning

- Risk of Electric Shock
- Turn power off before inspection, installation or removal.
- Risk of Burn
- Allow lamp to cool before handling
- Turn power off before installing lamp.
- Risk of Fire
- Keep combustible materials away from lamp.
- Use in enclosed fixture rated for this product.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
- Do not exceed 110% of rated voltage.
- Do not touch glass with bare hands.
- Do not use lamp if outer glass is scratched or broken.
- Use eye protection when handling lamp.
- Use in enclosed fixture rated for this product.