



Product Number: 58846

Order Abbreviation: 6.6A/45T3.5/64320/EXM

General Description: 45 WATT, TUNGSTEN HALOGEN, CURRENT CONTROLLED, SINGLED-END, BI-PIN, AIRFIELD

Product Information

Abbrev. With Packaging Info.	66A45T3564320EXM 12/CS 1/SKU
ANSI Code	EXM
Application	Airfield/Airport
Average Rated Life (hr)	1500
Base	GZ9.5 Bipin Prefocus
Bulb	T11,5
Class	C (gas)
Color Rendering Index (CRI)	100
Color Temperature (K)	3200
Current (A)	6.6
Diameter d (in)	0.453
Diameter d (mm)	11.50
Filament	C-8
Filament Dimensions Length (in)	.130
Filament Dimensions Length (mm)	3.3
Filament Dimensions Width (in)	.055
Filament Dimensions Width (mm)	1.4
Lamp Finish	Clear
Light Center Length - LCL (in)	1.0
Light Center Length - LCL (mm)	25.4
Luminous Flux (lm)	875
Maximum Overall Length - MOL (in)	1.752
Maximum Overall Length - MOL (mm)	44.5
Nominal Wattage (W)	45.00
Operating Position	s 90
Type of Current	AC

Footnotes

- s (Operating Position) = Vertical, base down
- p (Operating Position) = Horizontal