

30281 - EAL

GE R40 - Photofloods









CAUTIONS & WARNINGS

Caution

- Risk of Burn
- Allow lamp/fixture to cool before handling.
- Turn power off before installing lamp.
- Lamp may shatter and cause injury if broken
- Dispose of lamp in a closed container.
- Do not use lamp if outer glass is scratched or broken.

Warning

- Risk of Electric Shock
- Turn power off before inspection, installation or removal.
- Risk of Fire
- Keep combustible materials away from lamp.
- Use in enclosed fixture rated for this product.
- \bullet Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
- Avoid direct water, liquid or metal contact.
- Do not exceed 110% of rated voltage.
- Do not use lamp if outer glass is scratched or broken.
- Use in enclosed fixture rated for this product.

GENERAL CHARACTERISTICS

Lamp Type Incandescent - Reflector

Bulb R40

Base Medium Screw (E26)

Filament CC-2V Rated Life (NOM) 15.0 h Primary Application Photofloods

PHOTOMETRIC CHARACTERISTICS

Center Beam Candlepower

(CBCP) (NOM)

Color Temperature (NOM) 3200.0 K

ELECTRICAL CHARACTERISTICS

Wattage (NOM) 500.0 Voltage (NOM) 120.0

DIMENSIONS

Maximum Overall Length

6.630 in(168.4 mm)

(MOL) (NOM)

Bulb Diameter (DIA) (NOM) 5.000 in(127.0 mm)

PRODUCT INFORMATION

Product Code 30281
Description EAL
ANSI Code EAL
Standard Package Case

Standard Package GTIN 10043168302811

Standard Package Quantity
Sales Unit
No Of Items Per Sales Unit
No Of Items Per Standard

24

Package

UPC 043168302814