

# 14311 - Q350T3/CL/HIR

GE Watt-Miser® T2.5

a product of ecomagination

Energy Savings







# **CAUTIONS & WARNINGS**

#### Caution

- Lamp may shatter and cause injury if broken
- Dispose of lamp in a closed container.
- Do not use lamp if outer glass is scratched or broken.

## Warning

- Lamp emits UV radiation which may cause eye/skin injury. RG-3
- Avoid exposure of eyes and skin to unshielded lamp.
- Risk of Electric Shock
- Turn power off before inspection, installation or removal.
- Risk of Burn
- Allow lamp to cool before handling.
- Turn power off before installing lamp.
- Risk of Fire
- Fire Hazard! Do not use in Torchieres or other indoor residential fixtures.
- Keep combustible materials away from lamp.
- Use in enclosed fixture rated for this product.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
- Do not exceed 110% of rated voltage.
- Do not touch glass with bare hands.
- Do not use lamp if outer glass is scratched or broken.
- Operate lamp only in specified position -- see instructions.
- Use eye protection when handling lamp.
- Use in enclosed fixture rated for this product.

# **GENERAL CHARACTERISTICS**

Lamp Type Bulb Base Filament

**Bulb Finish** 

Rated Life (NOM)

Halogen - Double-Ended T2.5 Recessed Single Contact (R7s) C-8 Clear 2000.0 h

#### **PHOTOMETRIC CHARACTERISTICS**

Initial Lumens (NOM)9600.0Color Temperature (NOM)3000.0 KNominal Initial Lumens per Watt27.42857(NOM)27.42857

# **ELECTRICAL CHARACTERISTICS**

Wattage (NOM) Voltage (NOM) Burn Position 350.0 130.0 Horizontal

# **DIMENSIONS**

Maximum Overall Length (MOL) (NOM) Bulb Diameter (DIA) (NOM) Light Center Length (LCL) (NOM) 4.688 in(119.1 mm) 0.312 in(7.9 mm) 2.250 in(57.2 mm)

## **PRODUCT INFORMATION**

Product Code Description Standard Package Standard Package GTIN Standard Package Quantity Sales Unit No Of Items Per Sales Unit No Of Items Per Standard Package UPC

043168143110