




GE  
Lighting

**23828 - Q1500T3/CL-12PK**

GE T3



#### CAUTIONS & WARNINGS

##### Caution

- Lamp may shatter and cause injury if broken
  - Dispose of lamp in a closed container.
  - Do not use lamp if outer glass is scratched or broken.

##### Warning

- Lamp emits UV radiation which may cause eye/skin injury. RG-3
  - Avoid exposure of eyes and skin to unshielded lamp.
- Risk of Electric Shock
  - Turn power off before inspection, installation or removal.
- Risk of Burn
  - Allow lamp to cool before handling.
  - Turn power off before installing lamp.
- Risk of Fire
  - Fire Hazard! Do not use in Torchieres or other indoor residential fixtures.
  - Keep combustible materials away from lamp.
  - Use in enclosed fixture rated for this product.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
  - Do not exceed 110% of rated voltage.
  - Do not touch glass with bare hands.
  - Do not use lamp if outer glass is scratched or broken.
  - Operate lamp only in specified position -- see instructions.
  - Use eye protection when handling lamp.
  - Use in enclosed fixture rated for this product.

#### GENERAL CHARACTERISTICS

Lamp Type	Halogen - Single-Ended
Bulb	T3
Base	Recessed Single Contact (R7s)
Filament	C-8
Rated Life (NOM)	2000.0 h

#### PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	33000.0
Color Temperature (NOM)	3050.0 K
Nominal Initial Lumens per Watt (NOM)	22.0

#### ELECTRICAL CHARACTERISTICS

Wattage (NOM)	1500.0
Voltage (NOM)	208.0
Burn Position	Horizontal

#### DIMENSIONS

Maximum Overall Length (MOL) (NOM)	10.063 in(255.6 mm)
Bulb Diameter (DIA) (NOM)	0.375 in(9.5 mm)
Light Center Length (LCL) (NOM)	6.250 in(158.8 mm)

#### PRODUCT INFORMATION

Product Code	23828
Description	Q1500T3/CL-12PK
Standard Package	BUNDLE
Standard Package GTIN	30043168238282
Standard Package Quantity	144
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	144
UPC	043168238281