

Photo Not Available





CAUTIONS & WARNINGS

Caution

- Lamp may shatter and cause injury if broken
- Dispose of lamp in a closed container.
- Do not use lamp if outer glass is scratched or broken.

Warning

- \bullet Lamp emits UV radiation which may cause eye/skin injury. RG-3
- Avoid exposure of eyes and skin to unshielded lamp.
- Risk of Electric Shock
- Turn power off before inspection, installation or removal.
- Risk of Burn
 - Allow lamp to cool before handling.
 - Turn power off before installing lamp.
- Risk of Fire
- Fire Hazard! Do not use in Torchieres or other indoor residential fixtures.
- Keep combustible materials away from lamp.
- Use in enclosed fixture rated for this product.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
- Do not exceed 110% of rated voltage.
- Do not touch glass with bare hands.
- Do not use lamp if outer glass is scratched or broken.
- Operate lamp only in specified position -- see instructions.
- Use eye protection when handling lamp.
- Use in enclosed fixture rated for this product.

GENERAL CHARACTERISTICS

Lamp Type Halogen - Single-Ended

Bulb T3

Base Recessed Single Contact

(R7s)
Filament C-8
Rated Life (NOM) 2000.0 h

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM) 21500.0 Color Temperature (NOM) 3050.0 K Nominal Initial Lumens per Watt 21.5

(NOM)

ELECTRICAL CHARACTERISTICS

Wattage (NOM) 1000.0 Voltage (NOM) 230.0 Burn Position Horizontal

DIMENSIONS

Maximum Overall Length 10.063 in(255.6 mm)

(MOL) (NOM)

Bulb Diameter (DIA) (NOM) 0.375 in(9.5 mm) Light Center Length (LCL) 6.125 in(155.6 mm)

(NOM)

PRODUCT INFORMATION

Product Code 43711

Description Q1000T3/CL-6PK

Standard Package BUNDLE

Standard Package GTIN 30043168437111
Standard Package Quantity 144

No Of Items Per Sales Unit

No Of Items Per Standard

144

Package

UPC 043168437110