





CAUTIONS & WARNINGS

Caution

- Risk of Burn
- Allow lamp to cool before handling.
- Turn power off before installing lamp.
- Lamp may shatter and cause injury if broken
- Dispose of lamp in a closed container.
- Do not use lamp if outer glass is scratched or broken.

Warning

- Lamp emits UV radiation which may cause eye/skin irritation.
- Avoid exposure of eyes and skin to unshielded lamp.
- Risk of Electric Shock
- Turn power off before inspection, installation or removal.
- Risk of Fire
- Keep combustible materials away from lamp.
- Use in enclosed fixture rated for this product.
- Unexpected lamp rupture may cause injury, fire, or property damage
- Use eye protection when handling lamp.
- Use in enclosed fixture rated for this product.
- Do not touch glass with bare hands.
- Do not use lamp if outer glass is scratched or broken.
- Do not exceed 110% of rated voltage.

GENERAL CHARACTERISTICS

Lamp Type Bulb Base Filament

Bulb Finish

Rated Life (NOM)

Halogen - Single-Ended T4 Miniature Candelabra Screw (E11) CC-2V Clear 750.0 h

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)1800.0Color Temperature (NOM)2950.0 KNominal Initial Lumens per Watt18.0(NOM)18.0

ELECTRICAL CHARACTERISTICS

Wattage (NOM)	100.0
Voltage (NOM)	120.0

DIMENSIONS

Maximum Overall Length (MOL) (NOM) Bulb Diameter (DIA) (NOM) Light Center Length (LCL) (NOM) 2.813 in(71.5 mm) 0.500 in(12.7 mm) 1.375 in(34.9 mm)

PRODUCT INFORMATION

Product Code Description ANSI Code Standard Package Standard Package GTIN Standard Package Quantity Sales Unit No Of Items Per Sales Unit No Of Items Per Standard Package UPC 44385 Q100CL/MC/2V ESN Case 10043168443859 6 Unit 1 6

043168443852