

Product 15165**Number:****Order** 65BR30/FL 120V**Abbreviation:****General** Incandescent BR30 Reflector Lamp Inside Frost Finish Medium Aluminum**Description:** Base 65Watt 120Volt Flood Beam 24Bulbs Per Case 1Bulb Per Package*** Full Case Required****Product Information**

Abbrev. With Packaging Info.	65BR30FL 120V 24/CS 1/SKU
Approx. Lumens	600
Average Rated Life (hr)	2000
Base	Medium
Beam Angle (deg)	60
Beam Type	WFL
Bulb	BR30
Centerbeam Candlepower (cp)	370
Class	C (gas)
Color Rendering Index (CRI)	100
Color Temperature/CCT (K)	2850
Diameter (in)	3.752
Diameter (mm)	95.30
Filament	CC-6
Lamp Finish	Reflector
Maximum Overall Length - MOL (in)	5.375
Maximum Overall Length - MOL (mm)	136.525
Nominal Voltage (V)	120.00
Nominal Wattage (W)	65.00

**Footnotes**

- Should not be used in equipment where base temperature will exceed 500F.
- Operate only in porcelain sockets.
- Should be shielded against moisture falling on bulb.
- May not give satisfactory performance if any accessory lighting equipment touches the glass bulb.