

# Reflector Flood

### Reflector 65W 120V BR30 FL 1CT

Philips Family of Specialty Incandescents provide the perfect light for dramatic accents and display lighting as well as general lighting in a variety of applications. These flood lamps produce homogeneous beams of high intensity for general illumination.

#### Product data

## General Characteristics

Base Medium [Single Contact Medium Screw]
Base Information Aluminum [Aluminum Base]
Bulb BR30

Bulb BR30
Bulb Finish Frosted
Filament Shape CC6 [Straight]

Operating Position Universal [Any or Universal (U)]

Main Application Indoor Reflector

Atmosphere Gas Life with 3h/day use 1.8 an

[years]

Estimated Energy Cost/YR 7.83 \$

## • Light Technical Characteristics

Beam Description Flood [Flood]
Beam Angle 55 D
Color Temperature 2710 K
Initial lumen 620 Lm

#### • Electrical Characteristics

Watts 65 W Voltage 120 V

#### • Product Dimensions

Max Overall Length 5 (MOL) - C

5.375 (max) in

Diameter D

Footnotes

Footnotes Incandescent Footnotes Incandescent

fluorescent lamps for energy savings.] 87 [Do not allow hot bulb to come in contact with liquid or metal parts of the fixture, as glass may shatter. Do not use outdoors. Do not operate in close proximity to flammable materials or those adversely affected by heat or drying. Operate only in heat resistant sockets. (87)]

905 [Consider the compact

# • Product Data

Product number
Full product name
Short product name
Pieces per Sku
eop\_pck\_cfg
Skus/Case
Bar code on pack
Bar code on case
Logistics code(s)

eop\_net\_weight\_pp

Refl 65W 120V BR30 FL 1CT 1 12 12 46677225193

Reflector 65W 120V BR30 FL 1CT


50046677225198 920681036369 0.001 kg

248765

3.75 in



# Dimensional drawing







E26



© 2014 Koninklijke Philips N.V. (Royal Philips) All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.