

Rough / Vibration Service

75W Med 120-130V A19 FR 1SL

Philips Family of Specialty Incandescents provide the perfect light for dramatic accents and display lighting as well as general lighting in a variety of applications.Rough Service incandescent lamps have an exceptionally strong filament for which a special filament wire is used, which makes these lamps extremely suitable for places where shocks, bumps and vibrations frequently occur. The clear version, with its completely visible filament, is a brilliant light source, whereas the inside-frosted lamp is used wherever well diffused light is required.

Product data

• General Characteristics

Base	Medium [Single Contact Medium Screw]
Base Information	Aluminum [Aluminum Base]
Bulb	A19
Bulb Finish	Frosted
Filament Shape	RC-9 [Reinforced Construction C-9]
Operating Position	Universal [Any or Universal (U)]
Main Application	Rough & Vibration Service
Atmosphere	Gas
Nominal Lifetime	1000 hr
Rated Lifetime	1000 hr
(hours)	

712 Lm

• Light Technical Characteristics

Initial lumen

• Electrical Characteristics

Watts	75 W
Voltage	120-130 V
Starting Time	0.0 s

• Environmental Characteristics

Energy Efficiency Label (EEL)

• Product Dimensions

Max Overall Length 3.938 (max) in (MOL) - C Diameter D 2.375 in

Е


• Product Data

Product number Full product name Short product name Pieces per Sku eop_pck_cfg Skus/Case Bar code on pack Bar code on case Logistics code(s) eop_net_weight_pp

293605 75W Med 120-130V A19 FR 1SL 75W Med 120-130V A19 FR 1SL 1 12 46677293604 50046677293609 920586334302 0.001 kg



Dimensional drawing



AI9



E26



Product	C (Max)	D (Norm)	D (Max)
RC 75W E26 120-130V A-19 RC-9 FR	-	-	-



 $\ensuremath{\mathbb{C}}$ 2014 Koninklijke Philips N.V. (Royal Philips) All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting