



43574 - H7554 BULK

GE PAR36 - Emergency Building Light; Emergency Building







CAUTIONS & WARNINGS

Warning

• Pressurized lamp--unexpected rupture may cause injury, fire, or property damage

- Dispose of lamp in a closed container.

- Do not use lamp if outer glass is scratched or broken.

GENERAL CHARACTERISTICS

Lamp Type Bulb Base Filament Rated Life (NOM) Primary Application Sealed Beam - PAR PAR36 Screw Terminals C-6 50.0 h Emergency Building

PHOTOMETRIC CHARACTERISTICS

Beam Spread - Horizontal Beam Spread - Vertical Max. Beam Candlepower (MBCP) (MAX) 30.0 - 10.0 ° 20.0 - 10.0 ° 1400.0

ELECTRICAL CHARACTERISTICS

| Wattage (NOM) | 20.0 |
|---------------|------|
| Voltage (NOM) | 6.0 |

DIMENSIONS

Maximum Overall Length
(MOL) (NOM)2.750 in(69.8 mm)Bulb Diameter (DIA) (NOM)4.500 in(114.3 mm)

PRODUCT INFORMATION

Product Code Description ANSI Code Standard Package Standard Package GTIN Standard Package Quantity Sales Unit No Of Items Per Sales Unit No Of Items Per Standard Package UPC 43574 H7554 BULK H7554 Case 10043168435748 60 Bulk 1 60

043168435741