




GE  
Lighting

## 20834 - Q50MR16C/NFL30

GE ConstantColor® Precise™ MR16



### CAUTIONS & WARNINGS

#### Caution

- Lamp may shatter and cause injury if broken
  - Dispose of lamp in a closed container.
  - Do not use lamp if outer glass is scratched or broken.

#### Warning

- Risk of Burn
  - Allow lamp/fixture to cool before handling.
  - Turn power off before installing lamp.
- Risk of Fire
  - Keep combustible materials away from lamp.
  - Use in enclosed fixture rated for this product-- see instructions.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
  - Do not touch glass with bare hands.
  - Do not use lamp if outer glass is scratched or broken.
  - Use eye protection when handling lamp.
  - Use in enclosed fixture rated for this product.

### GENERAL CHARACTERISTICS

Lamp Type	Halogen - MR
Bulb	MR16
Base	2-Pin (GX5.3)
Filament	C-6
Rated Life (NOM)	6000.0 h
Lamp Enclosure Type (LET)	Open or enclosed fixtures

### PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	850.0
Center Beam Candlepower (CBCP) (NOM)	2500.0
Color Temperature (NOM)	3050.0 K
Beam Spread (NOM)	30.0 °

### ELECTRICAL CHARACTERISTICS

Wattage (NOM)	50.0
Voltage (NOM)	12.0

### DIMENSIONS

Maximum Overall Length (MOL) (NOM)	1.875 in(47.6 mm)
Bulb Diameter (DIA) (NOM)	2.000 in(50.8 mm)

### PRODUCT INFORMATION

Product Code	20834
Description	Q50MR16C/NFL30
ANSI Code	EXK
Standard Package	BUNDLE
Standard Package GTIN	00043168208345
Standard Package Quantity	20
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	20
UPC	043168991230