




GE
Lighting

72548 - 200PS30RS/23/STG

GE saf-t-gard® 200/177 watt PS30 1-pack

- 130/120 volts
- GE saf-t-gard® bulbs feature a protective Teflon® coating that helps contain glass fragments if broken. Designed with heavy-duty, all-weather construction, these bulbs protect against shattering, rain breakage and splatter from oil and lubricants. GE saf-t-gard® bulbs are perfect for home use in kitchens, basements garages, workshops and enclosed exterior fixtures
- Lasts 0.9/2.4 years based on 3 hours per day usage
- Estimated yearly energy costs \$24.09/\$21.32 based on 3 hours per day \$0.11 per kWh
- Provides 3240/2495 lumens
- PS30 shape with medium base for use in rough service applications

Photo
Not Available



GENERAL CHARACTERISTICS

| | |
|---------------------|----------------------------------|
| Lamp Type | Incandescent - A-line |
| Bulb | PS30 |
| Base | Medium Screw (E26) |
| Filament | C-9 |
| Bulb Finish | Inside frost |
| Rated Life (NOM) | 1000.0/2600.0 h |
| Primary Application | Rough Service; Shatter-Resistant |

PHOTOMETRIC CHARACTERISTICS

| | |
|---------------------------------------|----------------|
| Initial Lumens (NOM) | 3100.0 /2495.0 |
| Nominal Initial Lumens per Watt (NOM) | 16.2 /14.09605 |

ELECTRICAL CHARACTERISTICS

| | |
|---------------|-------|
| Wattage (NOM) | 200.0 |
| Voltage (NOM) | 130.0 |

DIMENSIONS

| | |
|------------------------------------|--------------------|
| Maximum Overall Length (MOL) (NOM) | 8.060 in(204.7 mm) |
| Bulb Diameter (DIA) (NOM) | 2.375 in(60.3 mm) |
| Light Center Length (LCL) (NOM) | 6.000 in(152.4 mm) |

PRODUCT INFORMATION

| | |
|----------------------------------|------------------|
| Product Code | 72548 |
| Description | 200PS30RS/23/STG |
| Standard Package | Case |
| Standard Package GTIN | 10043168725481 |
| Standard Package Quantity | 60 |
| Sales Unit | Unit |
| No Of Items Per Sales Unit | 1 |
| No Of Items Per Standard Package | 60 |
| UPC | 043168725484 |