

**Product** 59078**Number:****Order** 6.6A/200T4Q/64386**Abbreviation:**

General 200 watt, tungsten haloge, current controlled, single ended,
Description: airfield

Product Information

Abbrev. With Packaging Info.	66A200T4Q64386 40/CS 1/SKU
Application	Airfield/Airport
Average Rated Life (hr)	1500
Base	G6.35 Bipin
Bulb	T13,5
Class	C (gas)
Color Rendering Index (CRI)	100
Color Temperature (K)	3200
Current (A)	6.6
Diameter d (in)	0.531
Diameter d (mm)	13.50
Filament	C BAR 6
Filament Dimensions Length (in)	0.268
Filament Dimensions Length (mm)	6.8
Filament Dimensions Width (in)	0.181
Filament Dimensions Width (mm)	4.6
Lamp Finish	Clear
LIF Code	J1/39
Light Center Length - LCL (in)	1.299
Light Center Length - LCL (mm)	33
Luminous Flux (lm)	4700
Maximum Overall Length - MOL (in)	1.850
Maximum Overall Length - MOL (mm)	47
Nominal Wattage (W)	200.00
Operating Position	s90
Type of Current	AC

Footnotes

- s (Operating Position) = Vertical, base down
- p (Operating Position) = Horizontal