

**Product** 49171**Number:****Order** QTP1X28T5UNVPSNNL**Abbreviation:**

General 1-lamp Universal Voltage electronic ballast for 28W T5 lamp,
Description: packaged 20 pieces per case, without leads

Product Information

Abbrev. With Packaging Info.	QTP1X28T5UNVPSNNL
Ballast Factor	1.00
Ballast Height H (in)	0.8660
Ballast Length L (in)	14.1340
Ballast Width W (in)	1.1810
Family Brand Name	QUICKTRONIC Professional
Input Current (Amps)	0.30
Nominal Voltage (V)	120.00
Nominal Voltage (V)	120-277V
Number of Lamps	1
Open Circuit Voltage (V)	<600
Power Factor	>0.98
Primary Lamp Type	FP28T5
Sound Rating	A
Starting Method	PROSTART
Starting Temperature - Fahrenheit	0
Starting Temperature - Celsius	-18
Total Harmonic Distortion (THD)	<10%
Wiring Method	WIRETRAP CONNECTORS
Total Maximum Wattage	31



QUICK60+SM
SYSTEM WARRANTY

QUICKSENSE[®]
... ..

PRO StartTM
PROGRAMMED TO START

Footnotes

- Data based on primary lamp types. See OSRAM SYLVANIA System Performance Guide for data on other lamp combinations.
- Remote Mounting up to 18 feet
- 70C Max Case Temperature
- UL Listed Class P, Type 1 Outdoor
- Ground ballast case

- Install in accordance with National Electric Codes
- Complies with FCC 47 CFR Part 18, Non-Consumer
- ANSI 62.41 Cat. A Transient Protection
- Class A Sound Rating.
- Minimum Starting Temperature: 0F/-18C.
- Input Frequency: 50/60Hz.
- Complies with UL935 requirements for "Type CC" rating