

**Product** 49150**Number:****Order** QTP1X80T5/HO UNV PSN**Abbreviation:****General** 1-lamp Universal Voltage electronic ballast for 80W T5HO lamp**Description:** with pre-inserted lead wires, packaged 10 pieces per case**Product Information**

Abbrev. With Packaging Info.	QTP1X80T5HOUNVPSN
Ballast Factor	0.8
Ballast Height H (in)	0.8700
Ballast Length L (in)	14.1700
Ballast Width W (in)	1.1800
Circuit Type	Series
Family Brand Name	QUICKTRONIC Professional
Input Current (Amps)	0.00
Nominal Voltage (V)	120.00
Nominal Voltage (V)	120-277V
Number of Lamps	2
Power Factor	>0.98
Primary Lamp Type	FP80T5HO
Sound Rating	A
Starting Method	PROStart
Starting Temperature - Fahrenheit	0
Starting Temperature - Celsius	-18
Total Harmonic Distortion (THD)	<10%
Wiring Method	Leads
Total Maximum Wattage	90


QUICK60+SM
SYSTEM WARRANTY
QUICKSENSE[®]
... ..
PROStartTM
PROGRAMMED TO START
Footnotes

- Data based on primary lamp types. See OSRAM SYLVANIA System Performance Guide for data on other lamp combinations.
- Remote Mounting up to 10 feet
- 70C Max Case Temperature
- UL Listed Class P, Type 1 Outdoor
- Ground ballast case

- Install in accordance with National Electric Codes
- Complies with FCC 47 CFR Part 18, Non-Consumer
- ANSI 62.41 Cat. A Transient Protection
- Class A Sound Rating
- Input Frequency: 50/60Hz.
- Minimum Starting Temperature: 32F/0C.