

Product 49418
Number:

Order QTP2X54T5HO UNVPS80SC
Abbreviation:

General 2-lamp Universal Voltage electronic ballast for 54W T5HO lamp with integral lead wires, packaged 10 pieces per case
Description:

Product Information

Abbrev. With Packaging Info.	QTP2X54T5HO UNVPS80SC
Ballast Factor	0.8
Ballast Height H (in)	1.1810
Ballast Length L (in)	9.4690
Ballast Width W (in)	1.6300
Circuit Type	SERIES
Family Brand Name	QUICKTRONIC Professional
Input Current (Amps)	0.00
Nominal Voltage (V)	120.00
Nominal Voltage (V)	120-277V
Number of Lamps	2
Power Factor	>0.98
Primary Lamp Type	FP54T5HO
Sound Rating	A
Starting Method	PROSTART
Starting Temperature - Fahrenheit	50
Starting Temperature - Celsius	10
Total Harmonic Distortion (THD)	<10%
Wiring Method	LEADS
Total Maximum Wattage	96



QUICK60+SM
SYSTEM WARRANTY

QUICKSENSE[®]

PROStartTM
PROGRAMMED TO LAST

Footnotes

- Data based on primary lamp types. See OSRAM SYLVANIA System Performance Guide for data on other lamp combinations.
- Remote Mounting up to 10 feet
- 70C Max Case Temperature
- UL Listed Class P, Type 1 Outdoor
- Ground ballast case

- Install in accordance with National Electric Codes
- Complies with FCC 47 CFR Part 18, Non-Consumer
- ANSI 62.41 Cat. A Transient Protection
- Class A Sound Rating
- Input Frequency: 50/60Hz.
- Minimum Starting Temperature: 32F/0C.