



Product Number:	49430
Order Abbreviation:	QHE 3X40DL/UNV ISN-SC
General Description:	QHE 3X40/DL UNV ISN SC

Product Information

Abbrev. With Packaging Info.	QHE3X40DLUNVISNSC 10/CS 1/SKU
Ballast Factor	1.07
Ballast Height H (in)	1.1810
Ballast Length L (in)	9.4690
Ballast Width W (in)	1.6300
Circuit Type	PARALLEL
Family Brand Name	QUICKTRONIC
Input Current (Amps)	0.00
Nominal Voltage (V)	120.00
Nominal Voltage (V)	120-277V
Number of Lamps	3
Power Factor	>0.98
Primary Lamp Type	FT40DI/28WSS/IS
Sound Rating	A
Starting Method	INSTANT START
Starting Temperature - Fahrenheit	0
Starting Temperature - Celsius	-18
Total Harmonic Distortion (THD)	<10%
Wiring Method	LEADS
Total Maximum Wattage	101

Footnotes

- Data based on primary lamp types. See OSRAM SYLVANIA System Performance Guide for data on other lamp combinations.
- Remote Mounting up to 18 feet
- 70C Max Case Temperature
- UL Listed Class P, Type 1 Outdoor
- Insulate unused leads
- Ground ballast case
- Lampholder must be shorted per diagram
- Install in accordance with National Electric Codes
- Complies with FCC 47 CFR Part 18, Non-Consumer
- ANSI 62.41 Cat. A Transient Protection

- Class A Sound Rating.
- Minimum Starting Temperature: 0F/-18C.
- Input Frequency: 60Hz.