

Product 49863**Number:****Order** QHE 2X32T8/UNV ISL-SC**Abbreviation:****General** 2-lamp 32wT8 High Efficiency Instant Start electronic ballast, universal voltage, low ballast factor,10-pk**Description:****Product Information**

Abbrev. With Packaging Info.	QHE2X32T8UNVISLSC 10/CS 1/SKU
Ballast Factor	0.78
Ballast Height H (in)	1.1810
Ballast Length L (in)	9.4690
Ballast Width W (in)	1.6810
Circuit Type	PARALLEL
Family Brand Name	QUICKTRONIC High-Efficiency
Input Current (Amps)	0.00
Nominal Voltage (V)	120.00
Nominal Voltage (V)	120-277V
Number of Lamps	2
Open Circuit Voltage (V)	<600V
Power Factor	>0.97
Primary Lamp Type	FO32/XP
Sound Rating	A
Starting Method	INSTANT START
Starting Temperature - Fahrenheit	-20
Starting Temperature - Celsius	-29
Total Harmonic Distortion (THD)	<10%
Wiring Method	Leads
Max Case Temperature	70°C
Total Maximum Wattage	49

**Footnotes**

- Data based on primary lamp types. See OSRAM SYLVANIA System Performance Guide for data on other lamp combinations.
- Remote Mounting up to 18 feet
- 70C Max Case Temperature
- Complies with FCC 47 CFR Part 18, Non-Consumer
- Input Frequency: 50/60Hz.

- Minimum starting temperature: -20 F / -29 C