

**Product** 49906**Number:****Order** QTP2X32T8/UNV-ISN-SC-B**Abbreviation:****General** QTP2x32T8UNVISNSCB 10/CS 1/SKU 2-lamp 32wT8**Description:** Instant Start electronic ballast, universal voltage, normal ballast factor, banded 10-pk**Product Information**

Abbrev. With Packaging Info.	QTP2X32T8UNVISNSCB 10/CS 1/SKU
Ballast Factor	0.88
Ballast Height H (in)	1.1810
Ballast Length L (in)	9.4690
Ballast Width W (in)	1.6930
Circuit Type	PARALLEL
Family Brand Name	QUICKTRONIC Professional
Input Current (Amps)	0.00
Nominal Voltage (V)	120.00
Nominal Voltage (V)	120-277V
Number of Lamps	2
Open Circuit Voltage (V)	<600V
Power Factor	>0.97
Primary Lamp Type	FO32/XP
Sound Rating	A
Starting Method	INSTANT START
Starting Temperature - Fahrenheit	-20
Starting Temperature - Celsius	-29
Total Harmonic Distortion (THD)	<10%
Wiring Method	LEADS
Max Case Temperature	70°C
Total Maximum Wattage	56

**Footnotes**

- Data based on primary lamp types. See OSRAM SYLVANIA System Performance Guide for data on other lamp combinations.
- 70C Max Case Temperature
- UL Listed Class P, Type 1 Outdoor

- Ground ballast case
- Lampholder must be shorted per diagram
- Install in accordance with National Electric Codes
- Complies with FCC 47 CFR Part 18, Non-Consumer
- ANSI 62.41 Cat. A Transient Protection
- Class A Sound Rating
- Input Frequency: 50/60Hz.
- High power factor
- Minimum starting temperature: 60 F / 16 C with SS lamps
- Minimum starting temperature: -20 F / -29 C
- Insulate unused leads individually for 600V
- CSA certified.
- ANSI C82.11 where applicable.
- NO PCB (Polychlorinated Biphenyl)
- Remote mounting up to 20 feet