

**Product** 50716**Number:****Order** QTP 4X32T8/UNV DIM-TCL**Abbreviation:****General** 4-Lamp universal voltage electronic dimming ballast for 32W T8 lamp  
**Description:****Product Information**

|                                   |                        |
|-----------------------------------|------------------------|
| Abbrev. With Packaging Info.      | QTP4X32T8UNVDIMTCL     |
| Ballast Factor                    | 0.88                   |
| Ballast Height H (in)             | 1.0000                 |
| Ballast Length L (in)             | 16.7320                |
| Ballast Width W (in)              | 1.6810                 |
| Circuit Type                      | Series                 |
| Family Brand Name                 | QUICKTRONIC POWERSENSE |
| Input Current (Amps)              | 0.00                   |
| Nominal Voltage (V)               | 120.00                 |
| Nominal Voltage (V)               | 120-277V               |
| Number of Lamps                   | 4                      |
| Open Circuit Voltage (V)          | <600V                  |
| Power Factor                      | >0.95                  |
| Primary Lamp Type                 | FO32/XP                |
| Sound Rating                      | A                      |
| Starting Method                   | PROStart               |
| Starting Temperature - Fahrenheit | 50                     |
| Starting Temperature - Celsius    | 10                     |
| Total Harmonic Distortion (THD)   | <10%                   |
| Wiring Method                     | Leads                  |
| Total Maximum Wattage             | 120                    |


**QUICK60+™**  
5 YEAR WARRANTY
**Footnotes**

- Dimming Range 100-5%
- UL Listed Class P, Type 1 Outdoor
- Insulate unused leads
- Ground ballast case

- Install in accordance with National Electric Codes
- Complies with FCC 47 CFR Part 18, Non-Consumer
- ANSI 62.41 Cat. A Transient Protection
- Class A Sound Rating
- Input Frequency: 50/60Hz.
- Minimum Starting Temperature: 50F/10C.
- Data shown is at full light output.
- Remote mounting up to 8 feet.