

**Product** 51435**Number:****Order** QTP 4X32T8/UNV PSX-SC**Abbreviation:****General** 4-lamp 32wT8 Programmed Rapid Start electronic ballast, universal**Description:** voltage, 0.71 ballast factor, 10-pk

Product Information

Abbrev. With Packaging Info.	QTP4X32T8UNVPSXSC
Ballast Factor	0.71
Ballast Height H (in)	1.1800
Ballast Length L (in)	9.5000
Ballast Width W (in)	1.6800
Circuit Type	SERIES
Family Brand Name	QUICKTRONIC Professional
Input Current (Amps)	0.00
Nominal Voltage (V)	120.00
Nominal Voltage (V)	120-277V
Number of Lamps	4
Open Circuit Voltage (V)	<600V
Power Factor	>0.98
Primary Lamp Type	FO32/XP
Sound Rating	A
Starting Method	Programmed Rapid Start
Starting Temperature - Fahrenheit	0
Starting Temperature - Celsius	-18
Total Harmonic Distortion (THD)	<10%
Wiring Method	Leads
Max Case Temperature	70°C
Total Maximum Wattage	93



Footnotes

- Data based on primary lamp types. See OSRAM SYLVANIA System Performance Guide for data on other lamp combinations.
- Product is a kit containing the core & coil, capacitor, ingitor (where required), brackets and mounting hardware
- Remote Mounting up to 18 feet
- Remote Mounting up to 12 feet
- Remote Mounting up to 10 feet

- Complies with FCC 47 CFR Part 18, Non-Consumer
- Input Frequency: 60Hz.
- Wiring diagram applies to instant start standard, low power (LP), PLUS, and HD10 ballast types.
- Complies with UL935 requirements for "Type CC" rating
- Oil Filled Capacitor
- Product contains installation instructions