





GE
Lighting

16098 - FLE5/2/CAC/827

GE Soft White B10 - Facilities; Retail Display; Hospitality; Office; Restaurant



CAUTIONS & WARNINGS

Warning

- Risk of Electric Shock
 - Do not open - no user serviceable parts inside.
 - Do not use where directly exposed to water or outdoors without an enclosed fixture.

NOTES

- Fluorescent lamp lumens decline during life
- Lumens on one piece self ballasted lamp systems are measured base up.
- Use only on 120V 60 Hz circuits. Do not use on dimming circuits, photocells or timers. Do not use in wet locations.

GENERAL CHARACTERISTICS

Lamp Type	Compact Fluorescent - Self-Ballasted
Bulb	B10
Base	Candelabra Screw (E12)
Bulb Finish	Soft white
Equivalent Wattage (NOM)	20.0 W
Rated Life (NOM)	6000.0 h
Starting Temperature (MIN)	-15.0 °C
Total Harmonic Distortion (THD) (NOM)	145.0 %
Mercury Content (NOM)	3.5 mg
Picograms of Mercury (NOM)	3645.8 pg
Primary Application	Chandelier;Facilities;Retail Display;Hospitality;Office;Restaurant

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	200.0
Mean Lumens (NOM)	160.0
Nominal Initial Lumens per Watt (NOM)	40.0
Color Temperature (NOM)	2700.0 K
Color Rendering Index (CRI) (NOM)	82.0

ELECTRICAL CHARACTERISTICS

Wattage (NOM)	5.0
Voltage (NOM)	120.0
Input Voltage (NOM)	120.0 V
Input Current (NOM)	0.085 A
Power Factor (NOM)	0.6

DIMENSIONS

Maximum Overall Length (MOL) (NOM)	4.800 in(121.9 mm)
Nominal Length (NOM)	4.800 in(121.9 mm)

PRODUCT INFORMATION

Product Code	16098
Description	FLE5/2/CAC/827
Standard Package	Case
Standard Package GTIN	10043168160985
Standard Package Quantity	10
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	10
UPC	043168160988