





GE
Lighting

20704 - FLE11/R20

GE Floodlight Long Life Energy Smart® R20 - Facilities; Retail Display; Hospitality; Office; Restaurant

This product is no longer manufactured.

a product of
ecomagination



CAUTIONS & WARNINGS

Warning

- Risk of Electric Shock
 - Do not open - no user serviceable parts inside.
 - Do not use where directly exposed to water or outdoors without an enclosed fixture.

NOTES

- Amalgam product experience stable brightness over a wider temperature range and in various operating positions.
- Best performance if operated base up and at 77 degrees F (25C) ambient temperature.
- Fluorescent lamp lumens decline during life
- Lumens on one piece self ballasted lamp systems are measured base up.
- Use only on 120V 60 Hz circuits. Do not use on dimming circuits, photocells or timers. Do not use in wet locations.

GENERAL CHARACTERISTICS

Lamp Type	Compact Fluorescent - Self-Ballasted
Bulb	R20
Base	Medium Screw (E26)
Equivalent Wattage (NOM)	40.0 W
Rated Life (NOM)	10000.0 h
Starting Temperature (MIN)	-15.0 °C
Total Harmonic Distortion (THD) (NOM)	120.0 %
Mercury Content (NOM)	4.0 mg
Picograms of Mercury (NOM)	1315.8 pg
Primary Application	Indoor Floodlight;Facilities;Retail Display;Hospitality;Office;Restaurant

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	380.0
Mean Lumens (NOM)	304.0
Nominal Initial Lumens per Watt (NOM)	34.54545
Color Temperature (NOM)	2700.0 K
Color Rendering Index (CRI) (NOM)	82.0

ELECTRICAL CHARACTERISTICS

Wattage (NOM)	11.0
Input Voltage (NOM)	120.0 V
Power Factor (NOM)	0.6

DIMENSIONS

Maximum Overall Length (MOL) (NOM)	4.700 in(119.4 mm)
Nominal Length (NOM)	4.700 in(119.4 mm)

PRODUCT INFORMATION

Product Code	20704
Description	FLE11/R20
Standard Package	Case
Standard Package GTIN	10043168207048
Standard Package Quantity	10
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	10
UPC	043168207041