



GE
Lighting

49906 - FLE10HT3/2/SW/CD

GE energy smart® spiral® CFL 10 watt T3 spiral 1-pack

- Use original GE's Soft White when you need a light without glare and harsh shadows.
- Saves \$24.00 in energy costs*
- Lasts 8 times longer than a 40 watt regular soft white bulb*
- \$33 in energy savings over the life of the bulb based on 3 hours per day usage
- Energy Star Qualified
- Estimated yearly energy costs \$1.20 based on 3 hours per day \$0.11 per kWh
- Lasts 9.1 years based on 3 hours per day usage
- Save money and save energy with GE energy smart® spiral® CFL bulbs. GE energy smart® bulbs use 75% less energy than standard incandescents, helping you save money on energy. And, because they last 8 times longer than a standard incandescent, you'll replace these bulbs less often. Use general purpose GE energy smart® spiral® CFL bulbs in common household fixtures like table lamps, floor lamps and bare lamp sockets
- T3 spiral shape with medium base for use in table lamps and enclosed fixtures
- 40 watt replacement uses only 10 watts

a product of
ecomagination



Photo
Not Available

Rendering
Energy Savings

High Color

Photo
Not Available

GENERAL CHARACTERISTICS

Lamp Type	Compact Fluorescent - Self-Ballasted
Bulb	T3
Base	Medium Screw (E26)
Bulb Finish	Soft white
Equivalent Wattage (NOM)	40.0 W
Rated Life (NOM)	8000.0 h
Starting Temperature (MIN)	-15.0 °C
Total Harmonic Distortion (THD) (NOM)	120.0 %
Life in Years (NOM)	9.1
Mercury Content (NOM)	3.5 mg
Picograms of Mercury (NOM)	1041.7 pg
Primary Application	Standard;Facilities;Retail Display;Hospitality;Office;Restaurant

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	520.0
Mean Lumens (NOM)	420.0
Nominal Initial Lumens per Watt (NOM)	52.0
Color Temperature (NOM)	2700.0 K
Color Rendering Index (CRI) (NOM)	82.0

ELECTRICAL CHARACTERISTICS

Wattage (NOM)	10.0
Voltage (NOM)	120.0
Input Voltage (NOM)	120.0 V
Estimated Energy Cost per Year (NOM)	1.2
Input Current (NOM)	0.14 A
Power Factor (NOM)	0.6

DIMENSIONS

Maximum Overall Length (MOL) (NOM)	4.400 in(111.8 mm)
Nominal Length (NOM)	4.400 in(111.8 mm)

PRODUCT INFORMATION

Product Code	49906
Description	FLE10HT3/2/SW/CD
Standard Package	BUNDLE
Standard Package GTIN	30043168499065
Standard Package Quantity	12
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	12
UPC	043168499064



CAUTIONS & WARNINGS

Caution

- Lamp may shatter and cause injury if broken

For additional information, visit www.gelighting.com

- Remove and install by grasping only plastic portion of the lamp.

Warning

- Risk of Electric Shock

- Do not open - no user serviceable parts inside.
- Do not use where directly exposed to water.

*Guaranteed to last 5 years based on 4 hours use per day at 120V. Electricity cost savings based on rated life of 8,000 hrs compared to eight 40 watt Soft White incandescent bulbs (rated life 1000 hrs). Energy savings based on 10c per kilowatt hour. Reliable starting to 50F (-15oC). Lamp requires a short warm up period to reach full brightness.

NOTES

- Best performance if operated base up and at 77 degrees F (25C) ambient temperature.
- Fluorescent lamp lumens decline during life
- Lumens on one piece self ballasted lamp systems are measured base up.
- Most one piece self ballasted lamps for incandescent sockets and plug-in lamps with screw-in adapters do not work with clip-on shades
- Use only on 120V 60 Hz circuits. Do not use on dimming circuits, photocells or timers. Do not use in wet locations.