





GE
Lighting

80890 - FLE26HT3/2/XL827

GE Soft White Spiral® T3 - Facilities; Retail Display; Hospitality; Office; Restaurant

a product of
ecomagination



CAUTIONS & WARNINGS

Caution

- Lamp may shatter and cause injury if broken
 - Remove and install by grasping only plastic portion of the lamp.

Warning

- Risk of Electric Shock
 - Do not open - no user serviceable parts inside.
 - Do not use where directly exposed to water.

GENERAL CHARACTERISTICS

Lamp Type	Compact Fluorescent - Self-Ballasted
Bulb	T3
Base	Medium Screw (E26)
Equivalent Wattage (NOM)	100.0 W
Rated Life (NOM)	12000.0 h
Starting Temperature (MIN)	-15.0 °C
Mercury Content (NOM)	3.5 mg
Picograms of Mercury (NOM)	171.6 pg
Primary Application	Standard;Facilities;Retail Display;Hospitality;Office;Restaurant

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	1700.0
Mean Lumens (NOM)	1365.0
Nominal Initial Lumens per Watt (NOM)	65.38462
Color Temperature (NOM)	2700.0 K
Color Rendering Index (CRI) (NOM)	82.0

ELECTRICAL CHARACTERISTICS

Wattage (NOM)	26.0
Input Voltage (NOM)	120.0 V
Input Current (NOM)	0.37 A

DIMENSIONS

Maximum Overall Length (MOL) (NOM)	5.200 in(132.1 mm)
Nominal Length (NOM)	5.200 in(132.1 mm)

PRODUCT INFORMATION

Product Code	80890
Description	FLE26HT3/2/XL827
Standard Package	Case
Standard Package GTIN	10043168808900
Standard Package Quantity	10
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	10
UPC	043168808903