




GE  
Lighting

## 85382 - FLE10HT2/2/SW/CD

### GE energy smart® spiral® CFL 10 watt T2 spiral 1-pack

- \$39 in energy savings over the life of the bulb based on 3 hours per day usage
- 40 watt replacement uses only 10 watts
- Energy Star Qualified
- Estimated yearly energy costs \$1.20 based on 3 hours per day \$0.11 per kWh
- Lasts 11.0 years based on 3 hours per day usage
- Save money and save energy with GE energy smart® spiral® CFL bulbs. GE energy smart® bulbs use 75% less energy than standard incandescents, helping you save money on energy. And, because they last 8 times longer than a standard incandescent, you'll replace these bulbs less often. Use general purpose GE energy smart® spiral® CFL bulbs in common household fixtures like table lamps, floor lamps and bare lamp sockets
- T2 spiral shape with medium base for use in table lamps and enclosed fixtures
- Estimated yearly energy costs \$1.20 based on 3 hours per day \$0.11 per kWh



## GENERAL CHARACTERISTICS

Lamp Type	Compact Fluorescent - Self-Ballasted
Bulb	T2
Base	Medium Screw (E26)
Bulb Finish	Soft white
Equivalent Wattage (NOM)	40.0 W
Rated Life (NOM)	12000.0 h
Starting Temperature (MIN)	-15.0 °C
Life in Years (NOM)	11.0
Mercury Content (NOM)	3.5 mg
Picograms of Mercury (NOM)	628.6 pg
Primary Application	Standard;Facilities;Retail Display;Hospitality;Office;Restaurant

## PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	580.0
Mean Lumens (NOM)	464.0
Nominal Initial Lumens per Watt (NOM)	58.0
Color Temperature (NOM)	2700.0 K
Color Rendering Index (CRI) (NOM)	82.0

## ELECTRICAL CHARACTERISTICS

Wattage (NOM)	10.0
Input Voltage (NOM)	120.0 V
Estimated Energy Cost per Year (NOM)	1.2
Input Current (NOM)	0.16 A

## DIMENSIONS

Maximum Overall Length (MOL) (NOM)	3.700 in(94.0 mm)
Nominal Length (NOM)	3.700 in(94.0 mm)

## PRODUCT INFORMATION

Product Code	85382
Description	FLE10HT2/2/SW/CD
Standard Package	Case
Standard Package GTIN	10043168853825
Standard Package Quantity	3
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	3
UPC	043168853828

## CAUTIONS & WARNINGS

### Caution

- Lamp may shatter and cause injury if broken
  - Remove and install by grasping only plastic portion of the lamp.

### Warning

- Risk of Electric Shock
  - Do not open - no user serviceable parts inside.
  - Do not use where directly exposed to water.

## NOTES

- Best performance if operated base up and at 77 degrees F (25C) ambient temperature.
- Fluorescent lamp lumens decline during life
- Lumens on one piece self ballasted lamp systems are measured base up.
- Most one piece self ballasted lamps for incandescent sockets and plug-in lamps with screw-in adapters do not work with clip-on shades
- Use only on 120V 60 Hz circuits. Do not use on dimming circuits, photocells or timers. Do not use in wet locations.