



GE
Lighting

97565 - F13BX/E/841/ECO

GE Ecolux® Biax® T4 - Facilities; Retail Display; Hospitality; Office;
Restaurant; Warehouse

Photo
Not Available

Rendering
Energy Savings

High Color

Photo
Not Available



GENERAL CHARACTERISTICS

Lamp Type	Compact Fluorescent - Plug-In
Bulb	T4
Base	GX23
Equivalent Wattage (NOM)	60.0 W
Rated Life (Vert)	10000.0 h
Rated Life (NOM)	10000.0 h
Starting Temperature (MIN)	-20.0 °C
Mercury Content (NOM)	3.0 mg
Picograms of Mercury (NOM)	422.5352 pg
Additional Info	TCLP compliant
Primary Application	Facilities;Retail Display;Hospitality;Office;Restaurant;Warehouse

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (Vert)	825.0
Initial Lumens (NOM)	825.0
Initial Lumens (Hor)	63.46154
Mean Lumens (NOM)	710.0
Nominal Initial Lumens per Watt (NOM)	63.46154
Color Temperature (NOM)	4100.0 K
Color Rendering Index (CRI) (NOM)	82.0

ELECTRICAL CHARACTERISTICS

Wattage (NOM)	13.0
Voltage (MIN)	13.0
Voltage (NOM)	120.0
Lamp Current (NOM)	0.285 A
Current Crest Factor (MAX)	1.7

DIMENSIONS

Maximum Overall Length (MOL) (NOM)	7.000 in(177.8 mm)
Nominal Length (NOM)	7.000 in(177.8 mm)

PRODUCT INFORMATION

Product Code	97565
Description	F13BX/E/841/ECO
ANSI Code	60901-IEC-0013-1
Standard Package	BUNDLE
Standard Package GTIN	
Standard Package Quantity	100
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	100
UPC	043168975650

CAUTIONS & WARNINGS

Caution

- Lamp may shatter and cause injury if broken
 - Remove and install by grasping only plastic portion of the lamp.

NOTES

- Based on 60Hz reference circuit.
- Fluorescent lamp lumens decline during life