



GE  
Lighting

### 97572 - F13BX/850/ECO

GE Ecolux® Biax® T4 - Facilities; Retail Display; Hospitality; Office;  
Restaurant; Warehouse

Photo  
Not Available

Rendering  
Energy Savings

High Color



### GENERAL CHARACTERISTICS

|                            |                                                                    |
|----------------------------|--------------------------------------------------------------------|
| Lamp Type                  | Compact Fluorescent - Plug-In                                      |
| Bulb                       | T4                                                                 |
| Base                       | GX23                                                               |
| Equivalent Wattage (NOM)   | 60.0 W                                                             |
| Rated Life (NOM)           | 10000.0 h                                                          |
| Starting Temperature (MIN) | 0.0 °C                                                             |
| Mercury Content (NOM)      | 3.0 mg                                                             |
| Picograms of Mercury (NOM) | 444.4445 pg                                                        |
| Additional Info            | TCLP compliant                                                     |
| Primary Application        | Standard;Facilities;Retail Display;Hospitality;Office;Restaurant;W |

### PHOTOMETRIC CHARACTERISTICS

|                                       |          |
|---------------------------------------|----------|
| Initial Lumens (NOM)                  | 784.0    |
| Mean Lumens (NOM)                     | 675.0    |
| Nominal Initial Lumens per Watt (NOM) | 60.30769 |
| Color Temperature (NOM)               | 5000.0 K |
| Color Rendering Index (CRI) (NOM)     | 80.0     |

### ELECTRICAL CHARACTERISTICS


|                                |         |
|--------------------------------|---------|
| Wattage (NOM)                  | 13.0    |
| Voltage (NOM)                  | 59.0    |
| Lamp Current (NOM)             | 0.285 A |
| Current Crest Factor (MAX)     | 1.7     |
| Supply Current Frequency (NOM) | 60.0 Hz |

### DIMENSIONS

|                                    |                    |
|------------------------------------|--------------------|
| Maximum Overall Length (MOL) (NOM) | 7.300 in(185.4 mm) |
| Nominal Length (NOM)               | 7.000 in(177.8 mm) |
| Base Face to Top of Lamp (NOM)     | 6.690 in(169.9 mm) |

### PRODUCT INFORMATION

|                                  |                  |
|----------------------------------|------------------|
| Product Code                     | 97572            |
| Description                      | F13BX/850/ECO    |
| ANSI Code                        | 60901-IEC-0013-1 |
| Standard Package                 | BUNDLE           |
| Standard Package GTIN            |                  |
| Standard Package Quantity        | 100              |
| Sales Unit                       | Unit             |
| No Of Items Per Sales Unit       | 1                |
| No Of Items Per Standard Package | 100              |
| UPC                              | 043168975728     |





## **CAUTIONS & WARNINGS**

### **Caution**

- Lamp may shatter and cause injury if broken
  - Remove and install by grasping only plastic portion of the lamp.

### **NOTES**

- Based on 60Hz reference circuit.
- Fluorescent lamp lumens decline during life