

97601 - F18DBX/841/ECO4P

GE Ecolux® Biax® T4 - Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse











CAUTIONS & WARNINGS

Caution

- · Lamp may shatter and cause injury if broken
- Remove and install by grasping only plastic portion of the lamp.

GENERAL CHARACTERISTICS

Lamp Type Compact Fluorescent - Plug-

Bulb T4 Base G24q-2 Equivalent Wattage (NOM) 65.0 W

17000.0/20000.0 h Rated Life (NOM)

Starting Temperature (MIN) 0.0 °C Cathode Resistance (NOM) 6.05 Ohm Mercury Content (NOM) 3.0 mg Picograms of Mercury (NOM) 181.9 pg

Additional Info Dimmable with appropriate

dimming ballast./End of Life Protection (EOL)/TCLP

compliant Facilities:Retail

Primary Application

Display; Hospitality; Office; Restaurant; Wa

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM) 1250.0 Mean Lumens (NOM) 970.0 Nominal Initial Lumens per Watt 69.44444

(NOM)

Color Temperature (NOM) 4100.0 K Color Rendering Index (CRI) 82.0

(NOM)

ELECTRICAL CHARACTERISTICS

Wattage (NOM) 18.0 Voltage (NOM) 100.0 Current (max) (NOM) 5.25 A Open Circuit Voltage (after 220.0 V preheating) (MAX) 198.0 V

Open Circuit Voltage Across

Starter (MIN) Lamp Current (NOM) 0.22 A

Preheat Voltage (MIN) 4.25 V Current Crest Factor (MAX) 1.7 Supply Current Frequency 60.0 Hz

(NOM)

DIMENSIONS

Maximum Overall Length 5.800 in(147.3 mm) (MOL) (NOM) Nominal Length (NOM) 5.800 in(147.3 mm) Base Face to Top of Lamp 5.200 in(132.1 mm)

(NOM)

PRODUCT INFORMATION

Product Code 97601

Description F18DBX/841/ECO4P ANSI Code 60501-IEC-2518-2 **BUNDLE**

Standard Package

Standard Package GTIN Standard Package Quantity

50 Sales Unit Unit No Of Items Per Sales Unit 1 No Of Items Per Standard 50

Package

UPC 043168976015

NOTES

- 4-Pin lamp minimum starting temperature is a function of the ballast. Most ballasts are rated with a minimum starting temperature of 50 degrees F (10 C). Ballasts are also available that provide reliable starting to 0 degrees F (-18C) and -20 F (-29C).
- Based on 60Hz reference circuit.
- Cold cathode resistance is approximately 6.0 Ohms.
- Fluorescent lamp lumens decline during life