


# 97619 - F13TBX/827/A/ECO

GE Ecolux® Biax® T4 - Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse








#### **CAUTIONS & WARNINGS**

#### Caution

- · Lamp may shatter and cause injury if broken
- Remove and install by grasping only plastic portion of the lamp.

## **GRAPHS & CHARTS**

**Graphs\_Spectral Power Distribution** 



## **GENERAL CHARACTERISTICS**

Lamp Type

Bulb Base Equivalent Wattage (NOM) Rated Life (NOM) Cathode Resistance (NOM) Mercury Content (NOM) Picograms of Mercury (NOM) Rated Life (rapid start) @ Time Additional Info

Compact Fluorescent - Plug-In Τ4 GX24q-1 60.0 W 17000.0 h 10.5 Ohm 3.0 mg 233.7359 pg 20000.0 @ 12.0 h Dimmable with appropriate dimming ballast./End of Life Protection (EOL)/TCLP compliant Facilities;Retail Display;Hospitality;Office;Restaurant;W

Primary Application

#### **PHOTOMETRIC CHARACTERISTICS**

Initial Lumens (NOM)	900.0
Mean Lumens (NOM)	755.0
Nominal Initial Lumens per Watt	69.23077
(NOM)	
Color Temperature (NOM)	2700.0 K
Color Rendering Index (CRI)	82.0
(NOM)	

## **ELECTRICAL CHARACTERISTICS**

Wattage (NOM)	13.0
Voltage (NOM)	120.0
Current (max) (NOM)	5.25 A
Open Circuit Voltage (after	190.0 V
preheating) (MAX)	
Open Circuit Voltage Across	198.0 V
Starter (MIN)	
Lamp Current (NOM)	0.175 A
Preheat Voltage (MIN)	4.25 V
Current Crest Factor (MAX)	1.7
Supply Current Frequency	60.0 Hz
(NOM)	

## DIMENSIONS

Maximum Overall Length	4.300 in(109.2 mm)
(MOL) (NOM)	
Nominal Length (NOM)	4.200 in(106.7 mm)
Base Face to Top of Lamp	3.700 in(94.0 mm)
(NOM)	

## **PRODUCT INFORMATION**

Product Code Description Standard Package Standard Package GTIN Standard Package Quantity Sales Unit No Of Items Per Sales Unit No Of Items Per Standard Package UPC

043168976190

### NOTES

• 4-Pin lamp minimum starting temperature is a function of the ballast. Most ballasts are rated with a minimum starting temperature of 50 degrees F (10 C). Ballasts are also available that provide reliable starting to 0 degrees F (-18C) and -20 F (-29C).

Amalgam product experience stable brightness over a wider temperature range and in various operating positions.

• Based on 60Hz reference circuit.

· Fluorescent lamp lumens decline during life