





GE
Lighting

21738 - FLE26/2/R40/SWCD

GE Floodlight Soft White R40 - Facilities; Retail Display; Hospitality; Office; Restaurant

a product of
ecomagination



CAUTIONS & WARNINGS

Warning

- Risk of Electric Shock
 - Do not open - no user serviceable parts inside.
 - Do not use where directly exposed to water or outdoors without an enclosed fixture.

NOTES

- Best performance if operated base up and at 77 degrees F (25C) ambient temperature.
- Fluorescent lamp lumens decline during life
- Lumens on one piece self ballasted lamp systems are measured base up.
- Use only on 120V 60 Hz circuits. Do not use on dimming circuits, photocells or timers. Do not use in wet locations.

GENERAL CHARACTERISTICS

Lamp Type	Compact Fluorescent - Self-Ballasted
Bulb	R40
Base	Medium Screw (E26)
Equivalent Wattage (NOM)	90.0 W
Rated Life (NOM)	6000.0 h
Starting Temperature (MIN)	-15.0 °C
Total Harmonic Distortion (THD) (NOM)	170.0 %
Mercury Content (NOM)	3.5 mg
Picograms of Mercury (NOM)	560.9 pg
Primary Application	Indoor Floodlight;Facilities;Retail Display;Hospitality;Office;Restaurant

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	1300.0
Mean Lumens (NOM)	1040.0
Nominal Initial Lumens per Watt (NOM)	50.0
Color Temperature (NOM)	2700.0 K
Color Rendering Index (CRI) (NOM)	82.0

ELECTRICAL CHARACTERISTICS

Wattage (NOM)	26.0
Voltage (NOM)	120.0
Input Voltage (NOM)	120.0 V
Input Current (NOM)	0.36 A
Power Factor (NOM)	0.6

DIMENSIONS

Maximum Overall Length (MOL) (NOM)	6.500 in(165.1 mm)
Nominal Length (NOM)	6.500 in(165.1 mm)
Bulb Diameter (DIA) (NOM)	5.000 in(127.0 mm)

PRODUCT INFORMATION

Product Code	21738
Description	FLE26/2/R40/SWCD
Standard Package	Case
Standard Package GTIN	10043168217382
Standard Package Quantity	3
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	3
UPC	043168217385