





GE
Lighting

80895 - FLE26/2/PAR38/XL

GE Floodlight PAR38 - Facilities; Retail Display; Hospitality; Office; Restaurant

a product of
ecomagination



CAUTIONS & WARNINGS

Warning

- Risk of Electric Shock
 - Do not open - no user serviceable parts inside.

GENERAL CHARACTERISTICS

Lamp Type	Compact Fluorescent - Self-Ballasted
Bulb	PAR38
Base	Medium Screw (E26)
Equivalent Wattage (NOM)	100.0 W
Rated Life (NOM)	10000.0 h
Starting Temperature (MIN)	-15.0 °C
Life in Years (NOM)	9.1
Mercury Content (NOM)	3.5 mg
Picograms of Mercury (NOM)	269.2 pg
Primary Application	Pathway, Garden & Deck; Facilities; Retail Display; Hospitality; Office; Restaurant

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	1300.0
Mean Lumens (NOM)	1040.0
Nominal Initial Lumens per Watt (NOM)	50.0
Color Temperature (NOM)	2700.0 K
Color Rendering Index (CRI) (NOM)	82.0

ELECTRICAL CHARACTERISTICS

Wattage (NOM)	26.0
Input Voltage (NOM)	120.0 V
Estimated Energy Cost per Year (NOM)	3.13

DIMENSIONS

Maximum Overall Length (MOL) (NOM)	5.600 in(142.2 mm)
Nominal Length (NOM)	5.500 in(139.7 mm)
Bulb Diameter (DIA) (NOM)	4.750 in(120.6 mm)

PRODUCT INFORMATION

Product Code	80895
Description	FLE26/2/PAR38/XL
Standard Package	Case
Standard Package GTIN	10043168808955
Standard Package Quantity	6
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	6
UPC	043168808958