6/10/2014

Product Details

Product 20597 Number:

Order FT24DL/830/ECO Abbreviation:

GeneralDULUX 24W long compact fluorescent lamp with 4-pin base, 3000KDescription:color temperature, 82 CRI, ECOLOGIC for use on magnetic, electronic
and dimming ballasts

D	-	du	ot	Tn	fo	rm		1.	. 12
L.	10	uu	υı	111	10	1 111	au	10	ш

Abbrev. With Packaging Info.	FT24DL830ECO 10/CS 1/SKU			
Average Rated Life (hr)	12000			
Base	2G11			
Bulb	F (T5)			
Color Rendering Index (CRI)	80			
Color Temperature/CCT (K)	3000			
Diameter (in)	0.630			
Diameter (mm)	16.00			
Family Brand Name	Dulux® L			
Industry Standards	ANSI C78.901 - 2001			
Initial Lumens at 25C	1800			
Mean Lumens at 25C	1548			
Maximum Overall Length - MOL (in)	12.9			
Maximum Overall Length - MOL (mm)	326			
Nominal Wattage (W)	24.00			



Footnotes

- Approximate initial lumens after 100 hours operation.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.
- There is a NEMA supported, industry issue where T2, T4, and T5 fluorescent and compact fluorescent lamps operated on high frequency ballasts may experience an abnormal end-of-life phenomenon. This end-of-life phenomenon can result in one or both of the following: 1. Bulb wall cracking near the lamp base. 2. The lamp can overheat in the base area and possibly melt the base and socket. NEMA recommends that high frequency compact fluorescent ballasts have an end-of-life shutdown circuit which will safely and reliably shut down the system in the rare event of an abnormal end-of-life failure mode described above. The final requirements of this system are yet to be defined by ANSI. For additional information refer to NEMA papers on their WEBSITE at www.NEMA.org.
- The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified conditions and with ballast meeting ANSI specifications. If burning cycle is increased, there will be a corresponding increase in the average hours life.

Product Details

- These lamps may also be operated on rapid start circuits. On rapid start circuits the 24 watt lamp operates at 27 watts and the 36 watt lamp operated at 39 watts. Rated lamp life is unchanged.
- Rule of Thumb for Compact Fluorescent Lamps: Divide wattage of incandescent lamp by 4 to determine approximate wattage of compact fluorescent lamp that will provide similar light output.