

TUV PI -L

TUV PL-L 55W

TUV PL-L lamps are compact UVC (germicidal) lamps used in professional water and air disinfection units. The compact size of the lamp allows for a small system design and design flexibility. TUV PL-L lamps offer almost constant UV output over their complete lifetime, for maximum security of disinfection and high system efficacy. Thanks to the single-ended lamp base, lamp replacement is easy.

Product data

• General Characteristics

System Description High Frequency 2G11 Cap-Base Cap-Base Information 4 Pins Bulb 2xT16 Execution Main Application Disinfection

Useful Life 9000 hr

• Light Technical Characteristics

TUV Color Code Color Designation (text)

• Electrical Characteristics

55 W Watts 55 W Lamp Wattage Technical Lamp Voltage 103 V

Lamp Current 0.54 A

• UV-related Characteristics

UV-C Radiation 17.0 W

• Product Dimensions

Base Face to Base 505 (max) mm 530 (max) mm Insertion Length B 535 (max) mm Overall Length C 38 (max) mm Diameter D Diameter D1 18 (max) mm

• Product Data


eop_net_weight_pp

294645 Product number TUV PL-L 55W/4P HF 1CT Full product name Short product name TUV PL-L 55W/4P HF 1CT/25 Pieces per Sku 25 eop_pck_cfg 25 Skus/Case Bar code on pack 8711500633798 Bar code on case 8711500633804 927908704007 Logistics code(s)

134.000 gr




Dimensional drawing





TUV PL-L 55W

Product	A (Max)	B (Max)	C (Max)	D (Max)	D1 (Max)
TUV PL-L 55W/4P HF	505	530	535	38	18



Photometric data







Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.