



GE
Lighting




13968 - F15T8/SUN 6PK

GE closet & laundry 15 watt T8 1-pack

- Ideal for color critical areas or where sunlight is at a minimum.
- Full spectrum light
- 1.0 inch diameter T8 with medium bi-pin (g13) base
- 18 inches long
- 5000K sunshine light appearance
- Lasts 3.4 years based on 6 hours per day usage
- For use in task areas, closets and laundry rooms
- GE closet & laundry fluorescent bulbs provide very cool white light so you can get organized – whatever the task at hand. These bulbs are best for household laundry rooms and task areas and commercial workshops, clean rooms and light industrial areas
- Very cool light for task areas



High Color Rendering



CAUTIONS & WARNINGS

Caution

- Lamp may shatter and cause injury if broken
 - Wear safety glasses and gloves when handling lamp.
 - Do not use excessive force when installing lamp.

Warning

- Risk of Electric Shock
 - Turn power off before inspection, installation or removal.
- *Three year life based on rated life at 6 hours/day.

GRAPHS & CHARTS

Graphs_Lamp Mortality

GENERAL CHARACTERISTICS

| | |
|----------------------------|-------------------------------|
| Lamp Type | Linear Fluorescent - Straight |
| Bulb | Linear |
| Base | T8 |
| Rated Life (NOM) | Medium Bi-Pin (G13) |
| Bulb Material | 7500.0 h |
| Starting Temperature (MIN) | Soda lime |
| Mercury Content (NOM) | 10.0 °C |
| Picograms of Mercury (NOM) | 18.0 mg |
| Primary Application | 4571.4 pg |
| | Closet & Laundry |

PHOTOMETRIC CHARACTERISTICS

| | |
|---------------------------------------|----------|
| Initial Lumens (NOM) | 620.0 |
| Mean Lumens (NOM) | 525.0 |
| Nominal Initial Lumens per Watt (NOM) | 41.33333 |
| Color Temperature (NOM) | 5000.0 K |
| Color Rendering Index (CRI) (NOM) | 90.0 |

ELECTRICAL CHARACTERISTICS

| | |
|---|---------------|
| Wattage (NOM) | 15.0 |
| Open Circuit Voltage (rapid start) (MAX) | 220.0 V |
| Open Circuit Voltage (after preheating) Max @ Temperature | 210 V @ 10 °C |
| Open Circuit Voltage (rapid start) Min @ Temperature | 157 V @ 10 °C |
| Cathode Resistance Ratio - Rh/Rc (MIN) | 4.25 |
| Cathode Resistance Ratio - Rh/Rc (MAX) | 6.5 |
| Open Circuit Voltage (after preheating) Min @ Temperature | 108 V @ 10 °C |
| Current Crest Factor (MAX) | 1.7 |

DIMENSIONS

| | |
|--|---------------------|
| Maximum Overall Length (MOL) (NOM) | 17.780 in(451.6 mm) |
| Minimum Overall Length (NOM) | 17.670 in(448.8 mm) |
| Nominal Length (NOM) | 18.000 in(457.2 mm) |
| Bulb Diameter (DIA) (MIN) | 0.940 in(23.9 mm) |
| Bulb Diameter (DIA) (MAX) | 1.100 in(27.9 mm) |
| Bulb Diameter (DIA) (NOM) | 1.000 in(25.4 mm) |
| Max Base Face to Base Face (A) (NOM) | 17.220 in(437.4 mm) |
| Face to End of Opposing Pin (B) (MIN) | 17.400 in(442.0 mm) |
| Face to End of Opposing Pin (B) (MAX) | 17.500 in(444.5 mm) |
| End of Base Pin to End of Opposite Pin End (C) (NOM) | 17.670 in(448.8 mm) |

PRODUCT INFORMATION

| | |
|----------------------------------|----------------|
| Product Code | 13968 |
| Description | F15T8/SUN 6PK |
| ANSI Code | 2009-1 |
| Standard Package | BUNDLE |
| Standard Package GTIN | 30043168139688 |
| Standard Package Quantity | 24 |
| Sales Unit | Unit |
| No Of Items Per Sales Unit | 1 |
| No Of Items Per Standard Package | 24 |
| UPC | 043168139687 |

