

# 15479 - F17T8/XL/SP35/EC

#### GE Ecolux® Starcoat® T8

- Provides significantly longer life than standard lamp helping to reduce maintenance costs
- Passes TCLP, which can lower disposal costs.



Photo Not Available





# **CAUTIONS & WARNINGS**

#### Caution


- · Lamp may shatter and cause injury if broken
- Wear safety glasses and gloves when handling lamp.
- Do not use excessive force when installing lamp.

#### Warning

- Risk of Electric Shock
- Turn power off before inspection, installation or removal.

### **GRAPHS & CHARTS**

# Graphs\_Spectral Power Distribution



**Graphs\_Lumen Maintenance** 

#### **GENERAL CHARACTERISTICS**

Linear Fluorescent - Straight Lamp Type

Linear

Bulb

Base Medium Bi-Pin (G13) Rated Life (NOM) 40000.0 h Rated Life (instant start) @ 18000 h @ 3 h 24000 h @ 12 h

Rated Life (rapid start) @ Time 40000.0 @ 3.0/45000.0 @

12.0 h

1.4

**Bulb Material** Soda lime Starting Temperature (MIN) 10.0 °C Mercury Content (NOM) 2.95 mg 58.53175 pg Picograms of Mercury (NOM) Additional Info TCLP compliant **Primary Application** Full Wattage

#### PHOTOMETRIC CHARACTERISTICS

1325.0 Initial Lumens (NOM) Mean Lumens (NOM) 1260.0 Nominal Initial Lumens per Watt 77.94118

(NOM)

Color Temperature (NOM) 3500.0 K Color Rendering Index (CRI) 78.0

(NOM)

S/P Ratio (Scotopic/Photopic

Ratio) (NOM)

#### **ELECTRICAL CHARACTERISTICS**

Wattage (NOM) 17.0 Open Circuit Voltage (rapid 285.0 V start) (MAX)

Open Circuit Voltage (rapid 210 V @ 10 °C start) Min @ Temperature

Cathode Resistance Ratio - Rh/ 4.25

Rc (MIN)

Cathode Resistance Ratio - Rh/ 6.5

Rc (MAX)

Current Crest Factor (MAX) 1.7

## **DIMENSIONS**

Maximum Overall Length 24.000 in(609.6 mm)

(MOL) (NOM) Minimum Overall Length (NOM) Nominal Length (NOM) Bulb Diameter (DIA) (MIN) Bulb Diameter (DIA) (MAX)

24.000 in(609.6 mm) 0.940 in(23.9 mm) 1.100 in(27.9 mm) Bulb Diameter (DIA) (NOM) 1.000 in(25.4 mm) Max Base Face to Base Face 23.220 in(589.8 mm)

(A) (NOM)

Face to End of Opposing Pin 23.400 in(594.4 mm)

(B) (MIN)

Face to End of Opposing Pin

23.500 in(596.9 mm)

(B) (MAX)

End of Base Pin to End of

23.670 in(601.2 mm)

23.670 in(601.2 mm)

# Opposite Pin End (C) (NOM) **PRODUCT INFORMATION**

**Product Code** 15479

Description F17T8/XL/SP35/EC

1001-1 ANSI Code Standard Package Case

Standard Package GTIN 10043168154793

Standard Package Quantity 24 Sales Unit Unit No Of Items Per Sales Unit 1 No Of Items Per Standard 24

Package

**UPC** 043168154796

# Photo Not Available

**Graphs\_Lamp Mortality** 

Photo Not Available