



GE
Lighting



22747 - F30T8/KB 6PK

GE kitchen & bath 30 watt T8 1-pack

- For use in kitchens and baths
- Food looks fresher & skin tones are more attractive
- 1.0 inch diameter T8 with medium bi-pin (g13) base
- 3000K warm white light appearance
- 36 inches long
- For use in kitchens, bathrooms, and living areas
- GE kitchen & bath fluorescent bulbs deliver a warmer tone to create a comfortable and inviting atmosphere. These warm white bulbs are best for living areas throughout your home, hotels, commercial restrooms, reception areas and food preparation
- Lasts 3.4 years based on 6 hours per day usage
- Warm, inviting light that complements any decor



High Color Rendering



CAUTIONS & WARNINGS

Caution

- Lamp may shatter and cause injury if broken
 - Wear safety glasses and gloves when handling lamp.
 - Do not use excessive force when installing lamp.

Warning

- Risk of Electric Shock
 - Turn power off before inspection, installation or removal.
 - Avoid direct water/liquid contact.

*Three year life based on rated life at 6 hours/day.

GRAPHS & CHARTS

Graphs_Lamp Mortality

GENERAL CHARACTERISTICS

Lamp Type	Linear Fluorescent - Straight
Bulb	Linear
Base	T8
Rated Life (NOM)	7500.0 h
Bulb Material	Soda lime
Starting Temperature (MIN)	10.0 °C
Mercury Content (NOM)	8.0 mg
Picograms of Mercury (NOM)	558.5 pg
Primary Application	Kitchen & Bath

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	2125.0
Mean Lumens (NOM)	1910.0
Nominal Initial Lumens per Watt (NOM)	70.83333
Color Temperature (NOM)	3000.0 K
Color Rendering Index (CRI) (NOM)	70.0

ELECTRICAL CHARACTERISTICS

Wattage (NOM)	30.0
Open Circuit Voltage (after preheating) Max @ Temperature	375 V @ 10 °C
Cathode Resistance Ratio - Rh/Rc (MIN)	4.25
Cathode Resistance Ratio - Rh/Rc (MAX)	6.5
Open Circuit Voltage (after preheating) Min @ Temperature	176 V @ 10 °C
Current Crest Factor (MAX)	1.7

DIMENSIONS

Maximum Overall Length (MOL) (NOM)	35.780 in(908.8 mm)
Minimum Overall Length (NOM)	35.670 in(906.0 mm)
Nominal Length (NOM)	36.000 in(914.4 mm)
Bulb Diameter (DIA) (MIN)	0.940 in(23.9 mm)
Bulb Diameter (DIA) (MAX)	1.100 in(27.9 mm)
Bulb Diameter (DIA) (NOM)	1.000 in(25.4 mm)
Max Base Face to Base Face (A) (NOM)	35.220 in(894.6 mm)
Face to End of Opposing Pin (B) (MIN)	35.400 in(899.2 mm)
Face to End of Opposing Pin (B) (MAX)	35.500 in(901.7 mm)
End of Base Pin to End of Opposite Pin End (C) (NOM)	35.670 in(906.0 mm)

PRODUCT INFORMATION

Product Code	22747
Description	F30T8/KB 6PK
ANSI Code	2018-1
Standard Package	BUNDLE
Standard Package GTIN	00043168227476
Standard Package Quantity	24
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	24
UPC	043168982467

