

**Product** 23472**Number:****Order** F25T12/CW/RS/SS (F30T12CWRSSS)**Abbreviation:**

General 25W, T12 SUPER SAVER rapid start fluorescent lamp,
Description: Cool White phosphor, 4200K color temperature, 60 CRI, 6 pack, replaces F30T12 RS lamps. 18000 Avg rated life at 3 hrs/start, 28800 Avg rated life at 12 hrs/start

*** Full Case Required****Product Information**

Abbrev. With Packaging Info.	F25T12CWRSSS(F30T12CWRSSS) 30/CS 1/SKU
Actual Length (in)	35.780
Actual Length (mm)	908.81
Average Rated Life (hr)	18000
Base	Medium Bipin
Bulb	T12
Color Rendering Index (CRI)	60
Color Temperature/CCT (K)	4200
Diameter (in)	1.591
Diameter (mm)	40.40
Family Brand Name	SuperSaver®
Industry Standards	ANSI C78.81 - 2001
Initial Lumens at 25C	1925
Mean Lumens at 25C	1636
Nominal Length (in)	36.000
Nominal Length (mm)	914.40
Nominal Wattage (W)	25.00

Footnotes

- Recommended only for use on 2-lamp, 30 watt rapid-start high power factor lead, indoor ballasts that meet ANSI standards. Not intended for use: (1) at lamp ambient temperatures below 60 degrees F or in drafty locations, (2) on low power factor ballasts, (3) reduced current/reduced light output ballasts, (4) dimming ballasts, or (5) on inverter operated emergency lighting systems unless any of the above equipment is specifically listed for use with 25 watt lamps.
- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified conditions and with ballast meeting ANSI specifications. If burning cycle is increased, there will be a corresponding increase in the average hours life.