



Product 23484
Number:

Order F30T12/D35/RS
Abbreviation:

General 30W, T12 rapid start fluorescent lamp, Designer rare earth
Description: phosphor, 3500K color temperature, 70 CRI. 18000 Avg
rated life at 3 hrs/start

*** Full Case Required**

Product Information

| | |
|------------------------------|-------------------------|
| Abbrev. With Packaging Info. | F30T12D35RS 30/CS 1/SKU |
| Actual Length (in) | 35.780 |
| Actual Length (mm) | 908.81 |
| Average Rated Life (hr) | 18000 |
| Base | Medium Bipin |
| Bulb | T12 |
| Color Rendering Index (CRI) | 70 |
| Color Temperature/CCT (K) | 3500 |
| Diameter (in) | 1.591 |
| Diameter (mm) | 40.40 |
| Family Brand Name | Designer |
| Industry Standards | ANSI C78.81 - 2001 |
| Initial Lumens at 25C | 2250 |
| Mean Lumens at 25C | 1980 |
| Nominal Length (in) | 36.000 |
| Nominal Length (mm) | 914.40 |
| Nominal Wattage (W) | 30.00 |



Footnotes

- Average rated life is measured at 3 hours per start on 2-lamp, rapid start magnetic ballasts per IES recommended practice. Lamp life on single-lamp rapid start ballasts may be reduced.
- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified conditions and with ballast meeting ANSI specifications. If burning cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.