



**Product** 23618

**Number:**

**Order** F36T12/CW

**Abbreviation:**

**General** 30W, 36" MOL, T12 instant start Slimline fluorescent lamp,

**Description:** Cool White phosphor, 4200K color temperature, 60 CRI

**Product Information**

|                              |                      |
|------------------------------|----------------------|
| Abbrev. With Packaging Info. | F36T12CW 30/CS 1/SKU |
| Actual Length (in)           | 35.780               |
| Actual Length (mm)           | 908.81               |
| Average Rated Life (hr)      | 7500                 |
| Base                         | Single Pin           |
| Bulb                         | T12                  |
| Color Rendering Index (CRI)  | 60                   |
| Color Temperature/CCT (K)    | 4200                 |
| Diameter (in)                | 1.591                |
| Diameter (mm)                | 40.40                |
| Industry Standards           | ANSI C78.81 - 2001   |
| Initial Lumens at 25C        | 1970                 |
| Mean Lumens at 25C           | 1734                 |
| Mean Lumens at 35C           | 1734                 |
| Nominal Length (in)          | 36.000               |
| Nominal Length (mm)          | 914.40               |
| Nominal Wattage (W)          | 30.00                |

**Footnotes**

- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified conditions and with ballast meeting ANSI specifications. If burning cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.