

# 15622 - F35CW/U/6/WM/ECO


#### GE Cool White Ecolux® Watt-Miser® Mod-U-line® T12

- Passes TCLP, which can lower disposal costs.
- Saves energy compared to standard wattage lamps



Reduced Wattage Meets Federal Minimum Efficiency Standards





#### **CAUTIONS & WARNINGS**

#### Caution

• Improper handling may cause breakage.

- Do not carry lamp by bracket.
- Lamp may shatter and cause injury if broken
- Wear safety glasses and gloves when handling lamp.Do not use excessive force when installing lamp.


#### Warning

Risk of Electric Shock

- Turn power off before inspection, installation or removal.

# **GRAPHS & CHARTS**





**Graphs\_Lamp Mortality** 

# **GENERAL CHARACTERISTICS**

Lamp Type

Bulb Base Rated Life (NOM) Bulb Material Starting Temperature (MIN) Mercury Content (NOM) Picograms of Mercury (NOM) Additional Info Primary Application Linear Fluorescent - U-Shaped T12 Medium Bi-Pin (G13) 18000.0 h Soda lime 15.0 °C 5.0 mg 124.3 pg TCLP compliant Energy Saving

#### **PHOTOMETRIC CHARACTERISTICS**

Initial Lumana (NOM)	2600.0
Initial Lumens (NOM)	2600.0
Mean Lumens (NOM)	2235.0
Nominal Initial Lumens per Watt	76.47059
(NOM)	
Color Temperature (NOM)	4100.0 K
Color Rendering Index (CRI)	62.0
(NOM)	

# **ELECTRICAL CHARACTERISTICS**

Wattage (NOM)	35.0
Open Circuit Voltage (rapid	330.0 V
start) (MAX)	
Open Circuit Voltage (rapid	256 V @ 10 °C
start) Min @ Temperature	
Cathode Resistance Ratio - Rh/	4.25
Rc (MIN)	
Cathode Resistance Ratio - Rh/	6.5
Rc (MAX)	
Current Crest Factor (MAX)	1.7

# DIMENSIONS

Maximum Overall Length (MOL) (NOM) Minimum Overall Length (NOM) Nominal Length (NOM) Bulb Diameter (DIA) (NOM) Bulb Diameter in Bend (MIN) Bulb Diameter in Legs (MIN) Bulb Diameter in Legs (MIN) Bulb Diameter in Legs (MAX) Base Face to Top of Lamp (NOM) Lamp Legs Center to Center Length (NOM)

22.500 in(571.5 mm) 22.250 in(565.2 mm) 22.500 in(571.5 mm) 1.500 in(38.1 mm) 1.330 in(33.8 mm) 1.630 in(41.4 mm) 1.410 in(35.8 mm) 1.590 in(40.4 mm) 22.250 in(565.2 mm)

6.000 in(152.4 mm)

# **PRODUCT INFORMATION**

Product Code Description Standard Package Standard Package GTIN Standard Package Quantity Sales Unit No Of Items Per Sales Unit No Of Items Per Standard Package UPC

043168156226

