




GE
Lighting

68858 - F32T8/XL/SPX65E2

F32T8/XL/SPX65E2



GENERAL CHARACTERISTICS

Lamp Type	Linear Fluorescent - Straight
Bulb	Linear
Base	T8
Rated Life (NOM)	Medium Bi-Pin (G13)
Rated Life (instant start) @ Time	40000.0 h
Rated Life (rapid start) @ Time	25000 h @ 3 h
	36000 h @ 12 h
	40000.0 @ 3.0/45000.0 @ 12.0 h
Bulb Material	Sodalime glass
Starting Temperature (MIN)	10.0 °C
Mercury Content (NOM)	2.95 mg
Picograms of Mercury (NOM)	28.2567 pg
Primary Application	Full Wattage

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	2850.0
Mean Lumens (NOM)	2610.0
Nominal Initial Lumens per Watt (NOM)	89.0
Color Temperature (NOM)	6500.0 K
Color Rendering Index (CRI) (NOM)	78.0

ELECTRICAL CHARACTERISTICS

Wattage (NOM)	32.0
---------------	------

DIMENSIONS

Maximum Overall Length (MOL) (NOM)	48.000 in(1219.2 mm)
Nominal Length (NOM)	48.000 in(1219.2 mm)
Bulb Diameter (DIA) (NOM)	1.000 in(25.4 mm)

PRODUCT INFORMATION

Product Code	68858
Description	F32T8/XL/SPX65E2
Standard Package	Case
Standard Package GTIN	10043168688588
Standard Package Quantity	36
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	36
UPC	043168688581