



GE
Lighting

72114 - F32T8SPX30U6WMEC

GE Watt-Miser® Mod-U-line® T8 - Hospitality; Office; Restaurant; Retail Display; Warehouse



High Color Rendering
Meets Federal Minimum Efficiency Standards

Photo
Not Available

Circle E



GENERAL CHARACTERISTICS

Lamp Type	Linear Fluorescent - U-Shaped
Bulb	T8
Base	Medium Bi-Pin (G13)
Rated Life (NOM)	24000.0 h
Bulb Material	Soda lime
Starting Temperature (MIN)	15.0 °C
Mercury Content (NOM)	2.95 mg
Picograms of Mercury (NOM)	49.86477 pg
Additional Info	TCLP compliant
Primary Application	Hospitality;Office;Restaurant;Retail Display;Warehouse;Energy Saving

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	2800.0
Mean Lumens (NOM)	2465.0
Nominal Initial Lumens per Watt (NOM)	93.33333
Color Temperature (NOM)	3000.0 K
Color Rendering Index (CRI) (NOM)	82.0

ELECTRICAL CHARACTERISTICS



Wattage (NOM)	30.0
---------------	------

DIMENSIONS

Maximum Overall Length (MOL) (NOM)	22.500 in(571.5 mm)
Nominal Length (NOM)	22.500 in(571.5 mm)
Bulb Diameter (DIA) (NOM)	1.000 in(25.4 mm)

PRODUCT INFORMATION

Product Code	72114
Description	F32T8SPX30U6WMEC
Standard Package	Case
Standard Package GTIN	10043168721148
Standard Package Quantity	12
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	12
UPC	043168721141



GRAPHS & CHARTS

Graphs_Spectral Power Distribution

