




GE
Lighting

73292 - F28T8/XLSPX30ECO/CVG

F28T8/XLSPX30CVG-4 F28T8/XLSPX/ECO/CVGs



GENERAL CHARACTERISTICS

Lamp Type	Linear Fluorescent - Straight
Bulb	Linear
Base	T8
Rated Life (NOM)	Medium Bi-Pin (G13)
Rated Life (instant start) @ Time	45000.0 h
Rated Life (rapid start) @ Time	24000 h @ 3 h
	34000 h @ 12 h
	45000.0 @ 3.0/50000.0 @ 12.0 h
Bulb Material	Sodalime glass
Starting Temperature (MIN)	15.0 °C
Mercury Content (NOM)	2.95 mg
Picograms of Mercury (NOM)	29.67807 pg
Primary Application	Speciality

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	2643.0
Mean Lumens (NOM)	2485.0
Nominal Initial Lumens per Watt (NOM)	94.39286
Color Temperature (NOM)	3000.0 K
Color Rendering Index (CRI) (NOM)	85.0

ELECTRICAL CHARACTERISTICS

Wattage (NOM)	28.0
---------------	------

DIMENSIONS

Maximum Overall Length (MOL) (NOM)	48.000 in(1219.2 mm)
Nominal Length (NOM)	48.000 in(1219.2 mm)
Bulb Diameter (DIA) (NOM)	1.000 in(25.4 mm)

PRODUCT INFORMATION

Product Code	73292
Description	F28T8/XLSPX30ECO/CVG
Standard Package	Case
Standard Package GTIN	10043168732922
Standard Package Quantity	36
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	36
UPC	043168732925