

**Product** 21034**Number:****Order** FP28/835/ECO/SL**Abbreviation:**

General 28W, T5 PENTRON fluorescent lamp with Safeline coating. 3500K
Description: color temperature, rare earth phosphor, 85 CRI, ECOLOGIC

*** Full Case Required****Product Information**

Abbrev. With Packaging Info.	FP28835ECOSL 40/CS 1/SKU
Actual Length (in)	45.795
Actual Length (mm)	1163.19
Average Rated Life (hr)	20000
Base	Miniature Bipin
Bulb	T5
Color Rendering Index (CRI)	85
Color Temperature/CCT (K)	3500
Diameter (in)	0.669
Diameter (mm)	17.00
Family Brand Name	PENTRON® SAFELINE®
Initial Lumens at 25C	2550
Initial Lumens at 35C	2813
Mean Lumens at 25C	2372
Mean Lumens at 35C	2616
Nominal Length (in)	48.000
Nominal Length (mm)	1219.20
Nominal Wattage (W)	28.00
Life at 3 hrs./start on PRS ballasts	25000
Life at 12 hrs./start on PRS ballasts	30000

**Footnotes**

- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified conditions and with ballast meeting ANSI specifications. If burning cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.

- SYLVANIA ECOLOGIC fluorescent lamps are designed to pass the Federal Toxic Characteristic Leaching Procedure (TCLP) criteria for classification as non-hazardous waste in most states. TCLP test results are available upon request. Lamp disposal regulations may vary, check your local & state regulations. For more information, please visit www.lamprecycle.org
- SAFELINE lamps satisfy the criteria of having a non-shattering covering for prevention of glass and other lamp components in your product by containment within the safety coating material. The covering must be intact or the lamp must be replaced to be in compliance. An onsite inspector will require correction if the lamps are installed improperly or not maintained properly.
- SAFELINE lamps are intended for indoor use only. Lamps must be used in ambient temperatures below 135 degrees F. For T8 and T12 lamps, the coating is designed to withstand constant operating temperatures up to 239 degrees F and has a melting point in excess of 500 degrees F. For T5 lamps, the coating is designed to withstand constant operating temperatures up to 500 degrees F and has a melting point in excess of 620 degrees F. Lamps must be used in open fixtures with sockets that provide adequate lamp pin to socket contact. Lamps must not be used with defective ballasts sockets, or fixtures with improper wiring.