



**Product** 25154

**Number:**

**Order** F48T12/D35/HO

**Abbreviation:**

**General** 60W, 48" MOL, T12 HO (800 mA) rapid start fluorescent  
**Description:** lamp, Designer rare earth phosphor, 3500K color temperature, 70 CRI

**Product Information**

Abbrev. With Packaging Info.	F48T12D35HO 30/CS 1/SKU
Actual Length (in)	46.000
Actual Length (mm)	1168.40
Average Rated Life (hr)	12000
Base	Recessed Double Contact
Bulb	T12
Color Rendering Index (CRI)	70
Color Temperature/CCT (K)	3500
Diameter (in)	1.593
Diameter (mm)	40.46
Family Brand Name	Designer
Industry Standards	ANSI C78.81 - 2001
Initial Lumens at 25C	4250
Mean Lumens at 25C	3825
Mean Lumens at 35C	3825
Nominal Length (in)	48.000
Nominal Length (mm)	1219.20
Nominal Wattage (W)	60.00



**Footnotes**

- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified conditions and with ballast meeting ANSI specifications. If burning cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.
- Average life rating at 12 hours operation per start is 18,000 hours.